



MILLERS OILS

millersoils.co.uk

PRODUCT DATA SHEET

PREMIUM



AUTOMOTIVE



DATA SHEET NO: 7725

PRODUCT NAME/VISCOSITIES:

XF LONGLIFE 0w40

DESCRIPTION:

A high performance fully synthetic petrol and diesel engine oil.

APPLICATION:

Suitable for use in petrol and diesel engines. Formulated to be especially suitable for use in high performance vehicles, such as BMW, Mercedes-Benz, Porsche, Nissan GT-R 35 and Ford Focus RS 2.5 which require this grade and specification of lubricant.

USER BENEFITS:

- The high quality of this oil means that fuel economy is maximised at the same time as engine wear is being minimised. Oil viscosity or thickness is maintained even under the most severe of operating conditions thereby ensuring maximum engine protection.

PERFORMANCE PROFILE:

- ACEA A3 / B4
- API SN, CF
- Meets the requirements of BMW Longlife-01, MB 229.3, MB 229.5, VW 502 00, 505 00, Porsche A40, Renault RN0700, 0710, Chrysler MS-10725, Ford WSS-M2C937-A

TYPICAL CHARACTERISTICS:

SAE Grade	SAE 0w40
Specific Gravity @ 15°C	0.845
Kinematic Viscosity @ 100°C	13.5cSt
Kinematic Viscosity @ 40°C	84.6cSt
Viscosity Index	162
Pour point °C	-51
Flashpoint °C	>200
Cold Crank Viscosity @ -35°C	6,200cP max

HEALTH AND SAFETY:

Health and Safety Data Sheet 7725 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

Millers Oils Limited
Brighouse
West Yorkshire
HD6 3DP

Tel +44 (0)1484 713201
Fax +44 (0)1484 721263
Email enquiries@millersoils.co.uk
www.millersoils.co.uk

