

millersoils.co.uk

PRODUCT DATA SHEET

PREMIUM





DATA SHEET NO: 6229

PRODUCT NAME/VISCOSITIES:

XF LONGLIFE C2 5w30

DESCRIPTION:

A high performance fully synthetic mid SAPS (Sulphated Ash, Phosphorous, Sulphur) engine oil suitable for the latest petrol and diesel engine technology.

APPLICATION:

Suitable for use in petrol and diesel engines meeting Euro IV/V emission standard requiring ACEA C2 specification.

Manufacturer requirement for many Peugeot, Citroen and Renault vehicles, and preferred grade for many other manufacturers such as Fiat, Alfa Romeo, Chevrolet, Lancia, Lexus and Toyota.

USER BENEFITS:

- The high quality of this oil means that fuel economy is maximised at the same time as engine wear is being minimised. Oil viscosity or thickness is maintained even under the most severe of operating conditions thereby ensuring maximum engine protection.
- A mid SAPS formulation which is compatible with catalysts and diesel particulate filters (DPFs)

PERFORMANCE PROFILE:

- ACEA C2
- API SN, CF
- Meets the requirements of PSA B71 2290
- Fiat 9.55535-\$1

TYPICAL CHARACTERISTICS:

SAE Viscosity Grade 5w30

Specific Gravity @ 15°C 0.846

Kinematic Viscosity @ 100°C 10.3cSt

Kinematic Viscosity @ 40°C 57.2cSt Viscosity Index 171

Pour Point °C <-35 Flashpoint °C >200

Cold Crank Viscosity @ -35°C 6,600cP max

HEALTH AND SAFETY:

Health and Safety Data Sheet 6229 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

Millers Oils Limited Brighouse West Yorkshire Tel +44 (0)1484 713201 Fax +44 (0)1484 721263 Email

enquiries@millersoils.co.u www.millersoils.co.uk









For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk

Millers Oils Limited Brighouse West Yorkshire Tel +44 (0)1484 713201 Fax +44 (0)1484 721263 Email

enquiries@millersoils.co.uk
www.millersoils.co.uk



