



**MILLERS OILS**

millersoils.co.uk

PRODUCT DATA SHEET

**PREMIUM**



AUTOMOTIVE



DATA SHEET NO: 6231

**PRODUCT NAME/VISCOSITIES:**

**XF LONGLIFE C4 5w30**

**DESCRIPTION:**

A high performance fully synthetic low SAPS (Sulphated Ash, Phosphorous, Sulphur) engine oil suitable for the latest technology petrol and diesel engines.

**APPLICATION:**

Suitable for use in petrol and diesel engines meeting Euro IV/V emissions standards requiring ACEA C4 specification.

Required grade for latest Renault diesel engines with diesel particulate filters.

**USER BENEFITS:**

- The high quality of this fully synthetic oil means that fuel economy is maximised at the same time as engine wear is being minimised. Oil viscosity or thickness is maintained even under the most severe of operating conditions thereby ensuring maximum engine protection.
- A low SAPS formulation which is compatible with catalysts and diesel particulate filters (DPFs)

**PERFORMANCE PROFILE:**

- ACEA C4
- Meets the requirements of Mercedes-Benz 226.51
- Renault RN0720 (diesel + DPF)

Also for Suzuki and Nissan models requiring a C4 specification.

**TYPICAL CHARACTERISTICS:**

SAE Viscosity Grade	5w30
Specific Gravity @ 15°C	0.852
Kinematic Viscosity @ 100°C	12.0cSt
Kinematic Viscosity @ 40°C	71.7cSt
Viscosity Index	164
Pour point °C	<-30
Flashpoint °C	>200
Cold Crank Viscosity @ -30°C	6,600cP max

**HEALTH AND SAFETY:**

Health and Safety Data Sheet 6231 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

Millers Oils Limited  
Brighouse  
West Yorkshire  
HD6 3DP

Tel +44 (0)1484 713201  
Fax +44 (0)1484 721263  
Email [enquiries@millersoils.co.uk](mailto:enquiries@millersoils.co.uk)  
[www.millersoils.co.uk](http://www.millersoils.co.uk)

